



# Specifications RUBBER WALL BASE

**VPI Corporation**  
3123 S. 9th Street  
P.O. Box 451  
Sheboygan, WI 53082-0451, U.S.A.  
920-458-4664 • Fax 920-458-1368  
www.vpiflooring.com

## ACCEPTABLE MANUFACTURER

1. VPI Corporation, 3123 South 9<sup>th</sup> Street, P.O. Box 451, Sheboygan, WI 53082-0451

## FLOOR COVERING SPECIFICATION

1. VPI Rubber Wall Base MEETS ASTM F-1861-02 standards
2. VPI Rubber Wall Base Type TP Rubber, top set,
3. Cove or Straight base with sizes as follows:

Width: 2", 4"	Thickness: 1/8"	Lgths: 48"	PCS per CTN: 30 pcs. or 120 lf. / roll
---------------	-----------------	------------	--

Width: 6"	1/8"	Lgths: 48"	24 pcs. or 96 lf. / roll
-----------	------	------------	--------------------------

## MANUFACTURING SPECIFICATIONS

1. See all ASTM specifications per VPI web site: [www.vpiflooring.com](http://www.vpiflooring.com)
2. Meets VPI specific VOC, durability and other performance standards without exception or deviation

## ADHESIVE SPECIFICATIONS

1. VPI 600 acrylic wall base adhesive.
2. Use specified trowel and roller per VPI installation and maintenance instructions.

## PRE- INSTALLATION AND INSTALLATION SPECIFICATIONS

1. See VPI wall base installation and maintenance instructions for all installation requirements

## POST INSTALLATION SPECIFICATIONS

1. Prohibit traffic in area for 48 hours after installation.

## WARRANTY INFORMATION

1. 1 year warranty that products are free from defects in materials and workmanship.

**VPI Technical Service: (800) 874-4240**

Wall Base Rubber Specs 13: 03-20-13

