LONBEAD

LONSEAL

LONBEAD is a luxurious, textured, resilient sheet vinyl encased in pearlescent drops that is perfect for applications seeking a strong design statement. Chic and opulent, Lonbead's unique color palette makes a strong statement with embossing you'll want to reach out and touch.


*Due to the light color of #301 and #302, additional maintenance procedures are necessary to ensure a long lasting installation.

STANDARD SIZES (nominal)

Overall thickness: 0.100" (2.5 mm)
Wear layer thickness: 0.035" (0.9 mm)
Roll size: 6' (1.8 m) wide x 60' (18.3 m)
Weight: 0.8 lbs./sq. ft., 275 lbs./roll
Colors: Ten available

GREEN FEATURES

- GreenMedic™: Formulated for microbial resistance
- GreenAir™: Formulated for low VOCs
- 20 40% post-industrial recycled content
- Contributes towards LEED MR 4.1 and MR 4.2
- FloorScore[®] Indoor Air Quality Certified
- Conforms to CA Specification 01350
- . LEED Low Emitting Materials
- Adhesives and Sealants: IEQ Credit 4.1
- Flooring Systems: IEQ Credit 4.3



10-YEAR WARRANTY

TECHNICAL DATA

Sheet Vinyl Floor Covering with Backing, ASTM F1303	Type 1, Grade1, Class B
Flexibility, ASTM F137	Pass
Hardness, ASTM D2240	90
James Machine, SCOF, ASTM D2047	Neolite: 0.67; Neolite w/ Finish: 0.68
Abrasion Resistance, ASTM D3884	0.50%, 1,000 cycles
Static Load (max 0.005"), ASTM F970	1,000 psi
Short-term Indentation, ASTM F1914	0.000" residual indentation @ 75 lbs.
Castor Chair Test, ISO TR4918	25,000 cycles - Wear: 4.3, Color: 3.5, Change: 4.1
Dimensional Stability, ASTM F2199	0.15% loss
Heat Stability, ASTM F1514	Pass
Light Stability, ASTM F1515	Pass
Critical Radiant Flux, ASTM E648	Class 1 ≥0.45 watts/cm ²
Chemical Resistance, ASTM F925	No Change

For detailed technical information, please refer to www.lonseal.com.







LONSEAL, INC.
928 E. 238th Street, Carson, CA 90745 USA
800.832.7111 toll free | 310.830.7111 ph
www.lonseal.com



Updated: 04.14.14