

**I – PRODUCT NAME**

Versa Quartz

**II – MANUFACTURER**

Procedo Flooring  
1401 East 6<sup>th</sup> Street  
Tuscumbia, Alabama 35674  
Phone: 866-955-8291  
Fax: 419-436-4302  
Website: [www.procedoflooring.com](http://www.procedoflooring.com)

**III – PRODUCT DESCRIPTION**

Versa Quartz provides the durability and ease of maintenance the commercial flooring market demands. Made in the U.S.A. from natural materials, Versa Quartz combines creative esthetics with unmatched performance to provide a solution for any of your flooring needs.

Product is available in 12" x 12", 12" x 24" & 24" x 24" tiles with a smooth texture in .100" (2.5 mm) thickness.

**IV – TECHNICAL DATA**

*ASTM F 1066, Vinyl Composition Tile* – Meets or Exceeds All Requirements  
*ASTM E 648, Critical Radiant Flux* – > 1.08 W/cm<sup>2</sup>  
*ASTM E 662, Smoke Density* – < 450  
*ASTM E 2240, Hardness* – > 65, Shore D  
*ASTM D 2047, Slip Resistance* – ADA Compliant  
*ASTM F 925, Chemical Resistance* – Excellent  
*ASTM F 970, Modified Static Load* – 3500 PSI  
*ASTM F 510, Abrasion Resistance* – Excellent

**V – PRODUCT LIMITATIONS**

Do not install Versa Quartz in commercial kitchens or outdoors.

**VI – INSTALLATION**

Concrete subfloors should be dry, clean, smooth, level and structurally sound. Subfloors must be free of dust, oil, solvent, paint, wax, oil, grease, asphalt, sealers, curing and hardening compounds, alkaline salts, old adhesives, residue and other extraneous materials according to ASTM F 710.

Perform proper moisture testing prior to installation to determine moisture level. Refer to the adhesive information for the appropriate levels for the required adhesives. Use the ASTM F 2170 Relative Humidity method for moisture testing. If a moisture barrier is

needed, contact Technical Services for the appropriate material for use.

Deliver all materials to the installation location in original packaging with labels intact. The installation area and any stored materials should be maintained in 65°F to 85°F for at least 48 hours before installation, during installation, and thereafter. Proceed with the installation only when the conditions are proper and correct. Inspect all material for proper type and color. Perform a bond test at least 72 hours prior to the scheduled installation to ensure the surface is suitable.

Use only Procedo recommended adhesives to maintain all applicable warranties.

- Procedo PRO610 Spray Adhesive
- Procedo PRO620 Acrylic Adhesive
- Mapei® Ultrabond® G-21 Two-Part Reactive

Refer to complete product installation documentation for detailed instructions.

**VII – PRODUCT MAINTENANCE**

Please refer to the Versa Quartz Maintenance documentation for complete detailed procedures

**VIII – AVAILABILITY, COST & SAMPLES**

Products are available through Procedo Flooring appointed representatives. To locate the nearest representative, contact Customer Service at (866) 955-8291 or by email at [support@procedoflooring.com](mailto:support@procedoflooring.com)

**IX – TECHNICAL ASSISTANCE**

Obtain product data, installation instructions or additional Technical Assistance by contacting your Procedo representative or Customer Service at (866) 955-8291 or by email at [support@procedoflooring.com](mailto:support@procedoflooring.com)

**X – LIMITED WARRANTY**

Limited One (1) Year Manufacturers Warranty  
Limited Fifteen (15) Year Wear Warranty

Refer to [www.procedoflooring.com](http://www.procedoflooring.com) to obtain complete Technical, Installation, Maintenance & Warranty information.

